



RT670H (28.0w/cell)

HR (High Rate) series is especially designed for heavy load discharge applications with 5 years design life in float service. By using strong grids and specially designed active material the HR series offers stable performance during high current discharge requirements. The HR series offers 30% more power output than the standard range. Suitable for UPS/EPS where high current loads are required.




Specification

Cells Per Unit	3
Voltage Per Unit	6
Capacity	28W@15min-rate to 1.67V per cell @25°C
Weight	Approx. 1.2 Kg(Tolerance±4%)
Max. Discharge Current	70 A (5 sec)
Internal Resistance	Approx. 10 mΩ
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ± 5°C
Float charging Voltage	6.85 to 6.95 VDC/unit Average at 25°C
Recommended Maximum Charging Current	2.1 A
Equalization and Cycle Service	7.3 to 7.4 VDC/unit Average at 25°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for more than 6 months at 25°C. Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Terminal	Terminal F1/F2
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



Dimensions



Constant Current Discharge Characteristics : A(25°C)

F.V / Time	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
4.80V	30.49	22.55	20.27	14.72	12.07	8.890	5.007	3.953
5.00V	30.08	22.37	19.95	14.38	11.69	8.697	4.956	3.907
5.10V	29.16	21.02	18.89	13.81	11.45	8.490	4.801	3.804
5.25V	28.16	19.45	17.26	13.11	10.97	8.206	4.626	3.761
5.40V	25.99	18.06	15.45	12.52	10.67	7.159	4.450	3.641
5.55V	23.83	16.66	14.22	11.93	10.37	6.531	4.274	3.521

Constant Power Discharge Characteristics : W(25°C)


F.V / Time	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
4.80V	165.0	123.2	111.4	85.71	66.70	49.22	27.86	22.03
5.00V	164.7	123.0	110.6	84.21	65.21	48.45	27.62	21.80
5.10V	160.9	117.1	105.6	81.72	64.50	48.07	27.32	21.73
5.25V	156.9	109.9	98.2	79.18	62.92	47.17	26.84	21.64
5.40V	147.9	103.1	96.3	75.86	61.04	42.07	26.22	21.45
5.55V	138.9	96.2	94.42	72.53	59.17	39.06	25.61	21.26

All mentioned values are average values (Tolerance ±2%).


RT670H



Effect of temperature on long term float life



Storage characteristic




Supplementary charge required before use. (Carry out supplementary charge before use if 100% capacity is required)

Supplementary charge required before use. This supplementary charge will help to recover the capacity and should be made as early as possible.


Supplementary charge may often fail to recover the capacity. The battery should never be left standing till this state is reached

Supplementary charge and storage guidelines

Charge characteristic Curve for standby use



Discharge characteristic Curve



Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	6V&12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%
	2V	60%	75%	85%	88%	92%	99%	100%	103%	105%	106%
AGM Battery	6V&12V	46%	66%	76%	83%	90%	98%	100%	103%	107%	109%
	2V	55%	70%	80%	85%	92%	99%	100%	104%	108%	110%

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/cell	1.75V	1.70V	1.60V
Discharge Current (A)	(A) ≤ 0.2C	0.2C < (A) < 1.0C	(A) ≥ 1.0C

Charge the batteries at least once every six months, if they are stored at 25°C.

Charging Method:

Constant Voltage	-0.2Cx2h + 2.4~2.5V/Cellx24h, Max. Current 0.3CA
Constant Current	-0.2Cx2h + 0.1CAx12h
Fast	-0.2Cx2h + 0.3CAx4.0h

Maintenance & Cautions

Float Service:

- ※ Every month, recommend inspection every battery voltage.
- ※ Every three months, recommend equalization charge for one time.

Equalization charge method:

Discharge: 100% rate capacity discharge.

Charge: Max. current 0.3CA, constant voltage 2.4-2.45V/Cell charge 24h.

※ Effect of temperature on float charge voltage: -3mV/°C/Cell.

※ Length of service life will be directly affected by the number of discharge cycles, depth of discharge, ambient temperature and charging voltage.